

Management Development Institute Gurgaon

Date: 10/09/2024

Addendum-1:

Tender Ref. No.: MDIG/CC/2024-25/EPABX-NAB-GH/11 **Date:** 24.08.24

Tender Sub: Invitation of sealed quotations from reputed manufacturers or their authorized representatives for IP PBX at New Academic Block and Girls Hostel.

Please find below clarifications issued in the form of Addendum to the Tender. Kindly submit signed and stamped copy of this Addendum along with technical bid.

S. No.	Page No./ Clause No./ Sr.No.	Existing Description/ Query	Revised Description
1.	Page 29, S.No. 14	The system should have adapter-based power supply with output of 24V DC, 2.5A. It should have dual power supply port for Hot redundancy.	The offered system should have Dual power supply for HOT Redundancy and the offered system can work on AC/ DC Power source.
2.	Page 36, S.No. 209	Certification: CE, FCC, EMI- EMC, SAFETY, ROHS	Certifications CE, FCC, EMI-EMC, Safety , RoHS, TEC and MTCTE Approval required for Offered IP phones and TEC and MTCTE Approval required for offered IP PBX
3.	Page 36, S.No. 210	<ul style="list-style-type: none"> - 2 x 10/100/1000 Mbps LAN & PC Ports -Graphical LCD with Backlit -LED for Incoming/Ongoing Call, Mute, Hold -80 Programmable Keys -Intuitive User Interface with Icons -Multiple Languages Caller ID with Name, Number -45 or more keys including 4 Context Sensitive Hard Keys -RJ9 Handset Port, RJ9 Headset Port,3.5 mm Headset Port -Installation: Wall Mount, Table-top -CE, FCC-15, RoHS, Power over Ethernet (IEEE 802.3af) -Power Consumption: 5W (Typical)/Connector: DC Power Jack, 5VDC/600mA -Operating Temperature Range - 0 to 45°C -Storage Temperature - 0 to 55°C - Message wait Lamp, Ringer Lamp, 	<ul style="list-style-type: none"> - 2 x 10/100/1000 Mbps LAN & PC Ports - Graphical LCD with Backlit - LED for Incoming/Ongoing Call, Mute, Hold - 80 Programmable Keys - Intuitive User Interface with Icons - Multiple Languages Caller ID with Name, Number - 45 or more keys including 4 Context Sensitive Hard Keys - The offered IP phone should support Headset Port/ RJ-9 Headset Port or 3.5 MM Headset Port - Installation: Wall Mount, Table-top - CE, FCC-15, RoHS, Power over Ethernet (IEEE 802.3af) - Power Consumption: 5W (Typical)/Connector: DC Power Jack, 5VDC/600mA - Operating Temperature Range - 0 to 45°C - Storage Temperature - 0 to 55°C - Message wait Lamp, Ringer Lamp, Voice Mail, Call Pickup– Group and Selective, Paging TEC Approval required

		Voice Mail, Call Pickup– Group and Selective, Paging - TEC Approval required	
4.	Page 39, S.No.1 Financial Bid	IP PBX with Redundant CPU and Redundant Power Supply, Preloaded with Active 300 IP User licenses/ Expandable to 2000 IP Subscribers or more/ with atleast 100 Concurrent calls capability between different networks	IP PBX with redundant CPU & Redundant Power supply / Redundant Server with Redundant Power supply (HA) with 300 IP User License / Expandable to 2000 IP Subscribers or more with atleast 100 Concurrent calls capability between different networks